

# BEST SERIES SPRING LOADED CULTIVATOR



SMSL-2-13R



SMSL-2-13





## GENERAL FEATURES

It is manufactured as 7, 9, 11, 13, 15, 17 legs with double row and as 11, 13, 16, 17, 19 legs with 3-row with optional toothed rotating harrow combination. While breaking the stubble, it cultivates the soil without turning it over. In heavy soil, it cultivates the soil up to 250 mm depth. Distance between the legs can be fixed. The legs are made of high quality spring-steel and can stretch up to 60 mm. Due to having a 70 cm working height, it can't be blocked by stalks, weeds ext. during cultivation. It can't make a tough layer under the soil and it doesn't release the soil moisture since it doesn't turn over the soil during cultivation. It stores the minerals and oxygen because it works by vibrating. It raises the crops fruitfulness Rotating harrow combination levels the soil which the cultivator cultivates by pushing. It prepares a perfect seed bed and minimizes the seed casualty.

## TECHNICAL DETAILS

| CODE      | NUMBER OF LEG | NUMBER OF ROW | WORKING WIDTH (CM) | WORKING SPEED (KM/H) | REQUIRED POWER (HP) |
|-----------|---------------|---------------|--------------------|----------------------|---------------------|
| SMSL-2-7  | 7             | 2             | 205                | 5.5-9                | 50-60               |
| SMSL-2-9  | 9             | 2             | 265                | 5.5-9                | 60-70               |
| SMSL-2-11 | 11            | 2             | 305                | 5.5-9                | 70-80               |
| SMSL-2-13 | 13            | 2             | 345                | 5.5-9                | 80-90               |
| SMSL-2-15 | 15            | 2             | 395                | 5.5-9                | 90-100              |
| SMSL-2-17 | 17            | 2             | 440                | 5.5-9                | 100-120             |

| CODE      | NUMBER OF LEG | NUMBER OF ROW | WORKING WIDTH (CM) | WORKING SPEED (KM/H) | REQUIRED POWER (HP) |
|-----------|---------------|---------------|--------------------|----------------------|---------------------|
| SMSL-3-11 | 11            | 3             | 281                | 5.5-9                | 70-80               |
| SMSL-3-13 | 13            | 3             | 337                | 5.5-9                | 80-90               |
| SMSL-3-16 | 16            | 3             | 390                | 5.5-9                | 90-100              |
| SMSL-3-17 | 17            | 3             | 430                | 5.5-9                | 100-120             |
| SMSL-3-19 | 19            | 3             | 481                | 5.5-9                | 120-140             |



**SOIL MASTER**  
AGRICULTURAL MACHINERY

**HEAD OFFICE**

Add: Fevzi Cakmak Mh. 10758 Sk. No: 16/G  
42050 Karatay/Konya/TURKEY

T: +90 332 290 00 20  
F: +90 332 290 00 19

**FACTORY**

Add: Büyükkayacık Osb, Yaylacık Cd. No:  
23, 42250 Selcuklu/Konya/TURKEY

T: +90 332 239 18 85  
T: +90 332 239 18 86  
F: +90 332 239 18 87

[www.soilmaster.com.tr](http://www.soilmaster.com.tr)



+90 (532) 137 01 74



[info@soilmaster.com.tr](mailto:info@soilmaster.com.tr)



SOILMASTER AGRICULTURAL MACHINERY



For detailed information about  
our products, you can scan the  
QR code by your device.