

GRAND MASTER SERIES RUBBER TYPE MULTI DISC HARROW



SMRMD-24D



SMRMD-24R



SMRMD-32R



SMRMD-24D



SMRMD-32R





GENERAL FEATURES

Its open design with large clearances effectively prevents blockage even when working with high contents of organic matter. The serrated concave discs (510-570-620 mm diameter), which are supported by maintenance-free angular ball bearings, form the basis for the outstanding quality of work produced by this highly durable implement. The concave disc beams, which are located inside closed pockets and feature robust coil springs to protect them against overloads, ensure precise disc guidance even under difficult conditions. An impact harrow, which can be individually and finely adjusted, is provided behind the two rows of discs for precise deposition of the flow of soil. This improves the distribution of straw when driving at a diagonal angle to the direction of threshing.

TECHNICAL DETAILS

| CODE | MODEL OF LEG | DISC DIAMETER (CM) | WORKING WIDTH (CM) | WORKING DEPTH (MM) | REQUIRED POWER (HP) |
|----------|--------------|--------------------|--------------------|--------------------|---------------------|
| SMRMD-16 | RUBBER | 51/57/62 | 200 | 250 | 50-60 |
| SMRMD-18 | RUBBER | 51/57/62 | 225 | 250 | 60-70 |
| SMRMD-20 | RUBBER | 51/57/62 | 250 | 250 | 70-80 |
| SMRMD-22 | RUBBER | 51/57/62 | 275 | 250 | 80-90 |
| SMRMD-24 | RUBBER | 51/57/62 | 300 | 250 | 90-100 |
| SMRMD-26 | RUBBER | 51/57/62 | 325 | 250 | 100-110 |
| SMRMD-28 | RUBBER | 51/57/62 | 350 | 250 | 110-130 |
| SMRMD-32 | RUBBER | 51/57/62 | 400 | 250 | 120-150 |

| CODE | MODEL OF LEG | TYPE OF ROLLER | DISC DIAMETER (CM) | WORKING WIDTH (CM) | WORKING DEPTH (MM) | REQUIRED POWER (HP) |
|-----------|--------------|-------------------------------------|--------------------|--------------------|--------------------|---------------------|
| SMRMD-16R | RUBBER | HYDRAULIC FOLDABLE CAGE TYPE ROLLER | 51/57/62 | 200 | 250 | 50-60 |
| SMRMD-18R | RUBBER | | 51/57/62 | 225 | 250 | 60-70 |
| SMRMD-20R | RUBBER | | 51/57/62 | 250 | 250 | 70-80 |
| SMRMD-22R | RUBBER | | 51/57/62 | 275 | 250 | 80-90 |
| SMRMD-24R | RUBBER | | 51/57/62 | 300 | 250 | 90-100 |
| SMRMD-26R | RUBBER | | 51/57/62 | 325 | 250 | 100-110 |
| SMRMD-28R | RUBBER | | 51/57/62 | 350 | 250 | 110-130 |
| SMRMD-32R | RUBBER | | 51/57/62 | 400 | 250 | 120-150 |



SOIL MASTER
AGRICULTURAL MACHINERY

HEAD OFFICE

Add: Fevzi Cakmak Mh. 10758 Sk. No: 16/G
42050 Karatay/Konya/TURKEY

T: +90 332 290 00 20
F: +90 332 290 00 19

FACTORY

Add: Büyükkayacık Osb, Yaylacık Cd. No:
23, 42250 Selcuklu/Konya/TURKEY

T: +90 332 239 18 85
T: +90 332 239 18 86
F: +90 332 239 18 87

www.soilmaster.com.tr



+90 (532) 137 01 74



info@soilmaster.com.tr



SOILMASTER AGRICULTURAL MACHINERY



For detailed information about
our products, you can scan the
QR code by your device.